

INTEROPERABLE WORKSTATION | IWS

Overview

The Mutualink IWS provides an incident-based highly intuitive graphical user interface (GUI) used by a dispatcher or incident manager to communicate with other dispatch personnel and units in the field.

Choose IWS for maximum flexibility for a mobile workforce, as well as when you want to conserve dispatcher desk space. IWS runs on Windows and Mac desktops and laptops, as well as Apple and Android smartphones and some tablets.

IWS Web enables browser-based convenience without the need for a VPN.



- ✓ Android OS 7.0 or higher
- ✓ iOS 11.0 or higher
- ✓ Windows® 7, 8, 8.1, 10 (Windows RT not supported)
- ✓ macOS 10.7 and up
- ✓ Edge IWS Web: Desktop Chrome
- ✓ Graphic User Interface (GUI)
- ✓ Displays available partners and agency resources and active incidents
- ✓ Accommodates multiple incidents
- ✓ One video stream per incident is supported
- ✓ Real-time voice, video and data sharing
- ✓ End-to-End Encryption
- ✓ Locate and add partners using Network Map
- ✓ Monitor traffic and weather by activating layers on Network Map
- ✓ Manage incidents in Network Map view

macOS is a registered trademark of Apple, Inc. / Android is a trademark of Google, Inc. / iOS is a registered trademark of Cisco.

IWS APPLIANCES

IWS M500-100 Series
Desktop | 2RU



P-IWS M500-170 Series
Portable IWS



P-IWS M500-160 Series
Semi-Ruggedized Mobile IWS





MECHANICAL	IWS M500-100 SERIES	P-IWS M500-170 SERIES	P-IWS M500-160 SERIES
Size:	2.5" x 7.8" x 13"	1.1" x 14.8" x 10" with 15.6" screen	1.2" x 10.7" x 13.6
Weight:	6.2 lbs	5.4 lbs	4.4 lbs
Power:	110-240 VAC @ 50-60 Hz - 600 mA Typical 1.0A Max	Li-Ion battery pack with 48 WHr capacity and up to 9 hours of run time depending on configuration and usage. AC 100 V-240 V 50/60 Hz, auto sensing/switching world wide power supply	Li-Ion battery pack (typical 3220 mAh, min. 3050 mAh) with up to 11 hours of run time depending on configuration and usage. AC 100 V-240 V 50/60 Hz, auto sensing/switching worldwide power supply
Operating Environment:	0° to 50°C	5° to 35°C	-30° to +60° C
Processor Model/Speed:	Intel i5 4570TE, 2.7 GHz	Intel Core i5 6200U, 2.3 GHz	Intel Core i5-6300U, 2.4 GHz
Memory Type/Speed:	DDR3 1600 SO-DIMM 4 GB	DDR3 4 GB 1600 MHz	DDR3L SDRAM 8 GB
Drive Type and Size:	SSD 128	Hard Drive 500 GB	Hard Drive 256 GB
Operating System:	SELinux	SELinux	SELinux
Warranty:	1 Year Parts and Labor	1 Year Parts and Labor	1 Year Parts and Labor



For more information on any of our products or services please contact us:

 mutualink.net
 (866) 957-5465
 info@mutualink.net

 **Headquarters:**
 1269 South Broad Street
 Wallingford, CT 06492

 **Research & Development**
 3 Lan Drive
 Westford, MA 01886
 313 S. Jupiter Road, Suite 110
 Allen, TX 75002
 Rochelaise #26 Bo. Guanajibo
 Mayagüez, PR 00682

January 2022